

WARRANTY

The manufacturer warrants the product to be free from defects in materials and workmanship when installed, operated, and maintained in the manner instructed in this document. The Refresh shower filter is warranted for a period of 30 days from date of purchase. The manufacturer will repair or replace any shower filter that fails to perform due to faulty materials or workmanship. Items not covered under the warranty include: damage due to misuse, improper maintenance, improper installation, excessive water pressure or temperature, freezing, or general misapplication of the product's use and purpose. There are no warranties, expressed or implied, other than those stated herein. Rainshower is not liable in any way for any damages arising from the misuse or misapplication of this product. To make claims under this warranty, please contact your Rainshower dealer.



7251 Cathedral Rock Dr.,
Las Vegas, NV 89128
702.483.4410
www.rainshower.com

For shipping and orders: orders@rainshower.com • For new dealer inquiries, product questions, and general information: marketing@rainshower.com • For all other inquiries: headquarters@rainshower.com



INSTRUCTION GUIDE

Thank you for your purchase of Rainshower's Refresh Shower Filter.

NOTE: This product contains non-toxic granular filter media, produced within the regulations of The Safe Drinking Water Act (PL 99-339, June 19, 1986).

Some of the smallest grains of filtration media may shake out during shipping and handling. This is normal, and does not mean that the filter is defective or damaged in any way. When the filter is wet, the grains are held together and are not flushed out by the water flow during operation. The operational life of this product may vary depending on the quality of the source water and proper maintenance.

Areas with high levels of particulate matter in the source water or excessive scale buildup in the pipes may result in a reduction in water flow. This product and installation shall comply with state and local regulations, and is not intended for use as a drinking water treatment unit.

SPECIFICATIONS

SKU	NEWCEN-RS
Approximate Filter Capacity	30,000 gallons
Approximate Flow Rate	2.0 gpm
Housing Composition	ABS Plastic
Housing Dimensions	4" x 3"
Product Weight	17.6 oz
Filter Media	18 oz. KDF 55, Sediment Prefilter, Virgin Crystal Quartz
Working Pressure Range	30 psi (2.1 kg/cm2) to 100 psi (7.0 kg/cm2)
Operating Temperature Range	40° F (5° C) to 120° F (49° C)
Chlorine Reduction	90% or more

FEATURES

- The Refresh shower filter is designed to provide long-lasting performance for a variety of water conditions.

- Special crystalline quartz technology acts upon the water to create a softer feel and a more energizing experience.
- When used with an effective flow-reduction showerhead for optimal water delivery, this product can save water and energy costs.

INSTALLATION

1. Locate the red plastic plugs on each end of the Refresh and remove the plugs.
2. Remove the existing showerhead by rotating it counter-clockwise to unthread from the shower arm pipe.
3. If you use a manual shutoff valve with your shower arm, make sure that the shutoff valve is attached to the shower arm BEFORE the shower filter connection.
4. If your shower arm has an integral ball joint:
 - a. Replace the fixture with a standard 1/2" shower arm (available at most hardware stores), OR
 - b. Use an adapter (available at most hardware or plumbing supply stores) to connect the shower filter.
5. If your shower uses a handheld showerhead:
 - a. For a standalone handheld showerhead:
 - i. Attach the shower filter before the showerhead mount, or
 - ii. Attach the shower filter between the showerhead mount and the showerhead hose.

- b. For a showerhead with additional handheld showerhead: Attach the shower filter before the showerhead selector valve.
6. Attach the shower filter by threading it onto the shower arm and rotating clockwise by hand. HAND TIGHTEN ONLY. Do not overtighten.
7. Reconnect the showerhead by rotating it clockwise on the outlet connector (male thread) of the shower filter. HAND TIGHTEN ONLY. Do not overtighten.
8. Turn on the shower and allow water to run through the filter for 30 to 60 seconds before the first use.

LIMITATIONS

- This product is designed for use on potable systems only.
- This product effectively reduces free chlorine only.
- This product does not introduce anything harmful to the water.
- This product is not intended for use as a drinking water filter.
- Do not allow a wet filter to dry or to freeze
- Do not use any type of sequestering agent (polyphosphates) ahead of the filter.
- Product effectiveness may be reduced when used with water systems containing high levels of iron or with systems that use chemicals such as polyphosphates.